



TULIP

TRADING LLC

Personal Protective Equipment & Traffic Safety Equipment

Since 1988





Contents

PERSONAL PROTECTIVE EQUIPMENTS

◆ Head Protection	4
◆ Eye Protection	7
◆ Hearing Protection	11
◆ Respiratory Protection	12
◆ Face Protection	15
◆ Safety Vest	16
◆ Hand and Knee Protection	17
◆ Foot Protection	18
◆ Fall Protection	19

TRAFFIC MANAGEMENT

◆ Traffic Cones & Posts	24
◆ Barrier & Fencing	27
◆ Warning Lights & Beacons	29
◆ Warning Tapes	35
◆ Speed Ramps & Parking Accessories	37
◆ Warning Siren	39
◆ Sign Boards	40
◆ Lifting & Lashing Solutions	41
◆ Miscellenious	41



HEAD PROTECTION



Safety Helmet, JSP UK Model-EVO 8 (TS H 0001)

The strongest industrial safety helmet, this is the most advanced helmet in the world and conforms to CE EN 14052. It is the only helmet which provides side, front, rear and top protection.



Safety Helmet, JSP UK, Model-MK3 Slip Ratchet (TS H 0002)

These stylish helmets are tough, functional and offer an extremely comfortable 6 point terylene harness with slip ratchet adjustment. System offers a secure fit on the head for prolonged periods of use, hearing and face shield accessories can also be fitted. Conforms to EN 397, EN 50365, ANSI Z89, available in 8 colors.

Safety Helmet, JSP UK, Model-MK3 Wheel Ratchet. (TS H 0003)

These stylish helmets are tough, functional and offer an extremely comfortable 6 point terylene harness with wheel ratchet adjustment. System offers a secure fit on the head for prolonged periods of use, hearing and face shield accessories can also be fitted. Conforms to EN 397, EN 50365, ANSI Z89, available in 8 colors.



Safety Helmet, VIKING (TS H 0004)

This robust helmet is tough, functional and offers 6 point-standard poly harness with sweatband and slip ratchet adjustment. Conforms to EN 397:1995, available in 8 colors.

Safety Helmet, JSP UK, Model-EVO 2 (TS H 0005)

This latest evolution design helmet with a traditional six point polyethylene harness with a one touch slip ratchet and ventilation offers the most economical top level protection. Conforms to EN 397 and ANSI Z89, available in 6 colors.



Safety Helmet, JSP England, Model-EVO 3 (TS H 0006)

This latest evolution design helmet with a traditional six point comfort plus harness with an evolution wheel ratchet. Far tougher than any of its competitors. Conforms to EN 397 and ANSI Z89, available in 6 colors.



Safety Helmet, JSP England, Model-MK7 (TS H 0007)

The MK7 Model with super strong ventilated shell, functional and offer an extremely comfortable 6 point terylene harness with twist-lock wheel ratchet adjustment, system offering a secure fit on the head for prolonged period of use. hearing and face shield and integrated eyewear can also be fitted. Conforms EN397, EN50365, and ANSI Z89.1.

Safety Helmet, JSP UK, Model-Evolite (TS H 0008)

The Evolite Model with super strong lightweight ventilated ABS shell, functional and offer an extremely comfortable 6 point terylene harness with wheel ratchet/slip ratchet harness adjustment, also provide impact resistance up to 50 joules, temperature resistant $-30^{\circ}\text{C} \pm 50^{\circ}\text{C}$. Universal accessories. Integrated eyewear, reflective CR2 can also be fitted. Conforms to EN397, EN50365, and ANSI Z89.1. Weigh. 299 grams.



Safety Helmet - Fiberglass, VIKING (TS H 0009)

This tough helmet is made with a super strong fiberglass shell. Functional and light it offers an extremely comfortable 4 point terylene harness with wheel ratchet adjustment. It is the only fibreglass helmet ensuring a comfortable wear in hot conditions. Conforms to EN 397.

Safety Helmet, JSP UK, Model-MK7 with Retraspec (TS H 0010)

The JSP MK7 safety helmet is the ultimate in EN 397 head protection C/W Retraspec. The helmet with an integral visor ensures that eye protection is on hand when needed and never lost, whilst removing the need for additional eye protection. Protects to EN166.1.F.



Safety Helmet, JSP UK, Model-EVO6100 Full Brim (TS H 0011)

The EVO @ 6100 industrial safety helmet is the full brimmed addition to the Evolution® range of safety helmets. This industrial safety helmet incorporates JSP Ltd.'s iconic shield design and styling with the classic American styled full brim hard hat. The EVO@ 6100 full brim is dual specification by meeting both the European EN standard and the US ANSI standard.

Top Cap, JSP England (TS HC 0012)

A modern revolutionary and sporty protective bump cap designed as a safeguard against accidental bumping or scraping of the head. Protective bump cap which increases wearing capability. Inner HDPE liner with foam cushioning for protection and added comfort. Quick and easy to adjust. Conforms EN812.



Hard Cap A1+, JSP England (TS HC 0013)

The unique angled adjuster designed to fit under the occipital bone at the rear of the skull means that one size really does fit all, particularly when combined with the castellated protective removable liner, terry toweling sweatband. Very stylish and looks exactly like a baseball cap.

Chinstrap, JSP UK (TS CH 0014)

Elastic chinstrap suitable to fit for all JSP helmet.



Chinstrap China (TS CH 0015)

Elastic chinstrap china suitable for VIKING helmet.



Chinstrap with Guard (TS CH 0016)

Elastic chinstrap with chin guard china make suitable for VIKING helmet.



Rechargeable Head Lamp with 9 LED (TS HL 0017)

220volt rechargeable head lamp with elastic strap for to fit on the head or over the helmet as well.



EYE PROTECTION

Safety Spectacle, VIKING, Model-Aries (TS EP 0018)

Contour design, extremely light and comfortable. Poly carbonate lens, UV protection. Conforming to EN166, ANSI Z87.1, available in clear & dark lens.



Safety Spectacle, VIKING, Model-Alpine (TS EP 0019)

Contour design, extremely light and comfortable. Poly carbonate lens, UV protection. Conforming to EN166, ANSI Z87.1, available in clear & dark lens.



Safety Spectacle, VIKING, Model-Classic (TS EP 0020)

Poly carbonate lens, UV protection, wraparound with angle side protection. Conforming to EN166, ANSI Z87.1. 3 range extension function on the temple to offer better adjustment, available in clear & dark lens.



Safety Spectacle, VIKING, Model-PRO (TS EP 0021)

Poly carbonate lens, UV protection, over fit and wide vision design. Conforming to EN166, ANSI Z87.1, available in clear & dark lens.



Safety Spectacle, VIKING, Model-Stealth (TS EP 0022)

Poly carbonate lens, UV protection, over fit and wide vision design. Conforming to EN166, ANSI Z87.1, available in clear & dark lens.



Safety Spectacles, VIKING, Model-Cobra (TS EP 0023)

Modern design, poly carbonate lens, UV protection, soft flexible nose pad to ensure a comfortable fit and reduce slippage. Conforming to EN166, ANSI Z87.1, available in clear & dark lens.

Safety Spectacles, JSP UK, Model-Stealth 7000 (TS EP 0024)

Contour design and flexibility of frame gives a good versatile fit onto both smaller and larger faces. Extremely light and comfortable, Stealth7000 safety spectacle has been tested and approved to EN166 1.F.T (K or N) protection together with EN170 - UV Ultra violet ray filters or EN172 - Sun filters for industrial use. All lenses provide UV protection (Smoke lens version has UV protection up to 400nm UV400).



Safety Spectacles, JSP UK, Model-Stealth 8000 (TS EP 0025)

A lightweight safety spectacle, weighing just 26g, the wraparound 9 base curve polycarbonate lens has a built in adjustable PVC nose piece for added comfort and stability. Low profile tension control temples provide extra grip and are suitable for use with hearing protection. The temple tips have a spectacle cord anchor point for further practicality. UVA, UVB and UVC protection. EN166 1.F.K.N.

Safety Spectacles, JSP UK, Model-Cyber (TS EP 0026)

Scratch resistant with wraparound single piece lens, soft nose bridge. Duo-flex side arms with soft grip pads hold the spectacle comfortably in place. Conforms to EN166 1.F (K or N).



Safety Spectacles, JSP UK, Model-Stealth-9000 (TS EP 0027)

The Stealth™ 9000 is a lightweight safety spectacle, weighing just 25g, with a wrap-around 9 base curve polycarbonate lens. The slim stylish temples have been co-injection moulded with soft rubber to increase grip and provide excellent comfort levels. All of the Stealth™ 9000 safety spectacles come with class 1 optical lenses and block 99% of ultraviolet radiation.

Safety Spectacles, JSP UK, Model-Stealth Hybrid (TS EP 0028)

Stealth Hybrid™ offers eye protection in the form of a safety spectacle as well as safety goggles. With side arms attached the Stealth Hybrid™ is a safety spectacle providing protection to 1F standard and with the strap attached it is a safety goggle providing protection to the 1B standard. Both offer protection from UV, as well as increased dust and airborne particles compared with a standard safety spectacle.



Safety Spectacles, JSP UK Model-PA 800 (TS EP 0029)

The PA800 are twin lens, ultra-lightweight sports-styled safety spectacles. Extremely comfortable with a soft nose bridge and super soft dual material side arms that contour the head with a light but firm grip. Conforms to EN166 1.F.K.

Safety Spectacles, JSP UK, Model-9800 (TS EP 0030)

Adjustable temple length. Soft flexible nose pads to ensure a comfortable fit and reduce slippage. Modern safety spectacle with outstanding field of vision. Blocks 99.9% of ultraviolet radiation. Conforms to EN166.1.



**Safety Spectacles, JSP UK, Model-Visispec 9200 (OVER SPEC)
(TS EP 0031)**

A good all round safety spectacle giving excellent value for money. Clear polycarbonate lens and temples. Design doubles as a visitor spectacle. Conforms to EN 166.1.F.



Safety Spectacles, JSP UK, Model-Hydra Plus (TS EP 0032)

Wraparound eye shield for wide vision and complete protection. With vertically and horizontally adjustable ratcheting side arms. Conforms to EN166 1.F.T.

Safety Spectacles, JSP UK Model-Force Flex (TS EP 0033)

The force flex spectacle utilises a novel application of the very latest in plastic technology making them almost unbreakable. The frame of the spectacle is able to recover from almost any deformation that it may receive from simply being left in the wearer's pocket to being stood on. The frames also feature comfortable polymers where they touch the wearer's skin ensuring both a secure and comfortable fit. All units exceed the high optical standards for ANSI Z87.1, EN166 and AS/NZS meets the US Military requirements. 15 Calibri ballistic Impact test which exceeds EN166.F by over six times.



Safety Spectacles, JSP UK Model-9700 Sports (TS EP 0034)

Soft flexible nose pad and rubber temple tips ensure comfort fit and reduce slippage. Dual curved lens provide uncompromised wide vision and protection. Blocks 99.9% of ultraviolet radiation. Sporty modern design. Conforms to EN166.1.F.

**Safety Goggles, JSP UK Model-IDV Anti mist chemical goggles
(TS EP 0035)**

A compact and lightweight goggle. Tough polycarbonate lens offers high resistance to impact from flying particles. Vented body, cost effective, PVC frame, Polycarbonate lens. Conforms to EN 166.1.B.



Safety Goggles, JSP UK, Model-DV Martcare Impact goggles (TS EP 0036)

Compact and lightweight goggle. Tough polycarbonate lens offers high resistance to impact from flying particles. Vented body, cost effective, PVC frame, polycarbonate lens. Conforms to EN 166.1.B.

Safety Goggles, VIKING, Model-K2 (TS EP 0037)

Wide angle goggle features a wide elastic headband for improved comfort. Moulded-in ventilation for dust liquid, molten metal and hot solid protection. Conforms to EN166.1.B.3.4.



Safety Goggles, JSP UK, Model-Casplan (TS EP 0038)

The Casplan™ spherical lens goggle has been designed to offer a high degree of comfort for long periods where there is a significant risk of high speed particles striking the wearer in the eye. The goggle will resist the impact of a 6mm (¼") steel ball fired at 270mph (430kph) at the lens. Also protects the wearer from molten metal splash, liquid droplets and dust particles. Conforms to EN166.1.B.3.4.9 and ANSI Z87.1.



Safety Goggles, JSP UK, Model-Atlantic (TS EP 0039)

The deluxe anti-mist Atlantic™, wide angle goggle features a wide elastic headband for improved comfort. Moulded-in ventilation for dust liquid, molten metal and hot solid protection. Conforms to EN166.1.B.3.4.9.

Spectacles Cord (TS EP 0040)

Black quick release cord for attachment to all safety spectacles to ensure they are always close to hand.



Eye Wash Bottle, Rellwash (TS EP 0041)

500ml container of emergency eyewash; a sterile solution of Sodium 0.9 w/v (Normal Saline). Can be used to refill the wall-mounted stations.

Eye Wash Station with Mirror and 2 Bottles (TS EP 0042)

Complete with mirror and 2 x 500ml bottles of sterile solution of Sodium 0.9 w/v (Normal Saline).



Eye Wash Drum (TS EP 0043)

Gravity-flow portable eyewash features an integral full-flow nozzles that are activated by pushing down the black eyewash tray. Swing tray up to stop flow. Flows continually for up to 15 minutes. Includes polyethylene tank, 16-gallon capacity.

Eye Wash Bowl (TS EP 0044)

Eye wash hand/foot operated floor mounted.



Eye Wash Shower (TS EP 0045)

Eye wash shower, hand / foot operated, floor mounted.



HEARING PROTECTION

Ear Plug Corded, JSP UK (TS HP 0046)

Ear plug with cord, JSP UK, Self-adjusting to minimize pressure on the ear canal and to maximize noise protection. SNR = 33. Conforms to EN352-2.



Ear Plug Uncorded, JSP UK (TS HP 0047)

Ear plug without cord, JSP UK, self-adjusting to minimize pressure on the ear canal and to maximize noise protection. SNR = 33. Conforms to EN 352-2.

Washable Ear Plug China (TS HP 0048)

A triple flange design that hugs the ear canal and increases attenuation. These earplugs are washable and reusable, making them an economical choice. The advanced polymer material gives maximum comfort and durability so you get the most out of every wear.



Ear Defender, VIKING, Model-VED 1 (TS HP 0049)

Popular ear defender, suitable for light industrial duty and outdoor construction. SNR = 27db. Conforms to EN352 -1.

Ear Defender, VIKING, Model-VED2 (TS HP 0050)

Comfortable twin point mounted ear defenders this twin mounted system provides better distribution of pressure. Foam inserts provide extra comfort when in use. SNR = 28db.



Ear Defender, JSP UK, Model-Supamuff (TS HP 0051)

A popular choice of ear defender which offers effective, economical protection. Hygiene kits also available. Conforms to EN 352-1. SNR = 23.

Ear Defender, JSP UK, Model-Big Blue (TS HP 0052)

Quality ear defenders, for use in medium duty industrial and outdoor applications. Soft, wide foam cushions for all day comfort - ideal for long shifts. Over the head SNR=27. Behind the head SNR=26 Conforms to EN352-1.



Helmet Mounted Ear Defenders, JSP UK, Model-Inter GP (TS HP 0053)

Helmet mounted ear defenders designed for general purpose use. They are part of the new range of helmet mounted ear defenders from JSP. International slot compatibility means the InterGP™ fits the complete range of JSP safety helmets, and are even compatible with the JSP Surefit™ visor system. Easy to attach and detach with spring loaded arms that give an excellent fit to the ear. The steel arms maintain a constant and even pressure, whether hot or cold conditions, no matter how long user wears the cups for. When not in use the arms allow the cups to stand off clearly from the head. Conforms to EN 352-3.

Helmet Mounted Ear Defenders, JSP UK, Model-ThruXton (TS HP 0054)

Black to fit MK2 and MK3 helmets. SNR=26. Conforms to EN 352-3.



RESPIRATORY PROTECTION

Disposable Dust Mask, Comfort Mask (TS RP 0055)

Suitable for nuisance levels of non-toxic dust below the WEL only. This mask is ideal for applications where items in production need protecting from the wearer's breath, i.e. printed circuit board production. Does not offer respiratory protection.



Moulded Disposable Mask, VIKING-Model FFP2 Valved (TS RP 0056)

The valve products increase user comfort by lowering CO₂ and heat build-up. Class 2, medium efficiency (94%) with a protection factor of 10. With exhalation valve to increase comfort, soft polypropylene outer layer, elasticated head strap, adjustable nose clip. Conforms to EN149:2001.

Moulded Disposable Mask, JSP UK, Model-FFP2-122 Valved (TS RP 0057)

This "shaped to fit" quality range of moulded disposable masks are available in small, medium and large sizes. The valve products increase user comfort by lowering CO₂ and heat build-up. Class 2, medium efficiency (94%) with a protection factor of 10. with exhalation valve to increase comfort. Conforms to EN149:2001+A1: 2009.



Moulded Mask With Valve, JSP UK (TS RP 0058)

FFP3 Valved mask minimizes breathing resistance and maximizes the dust carrying capacity, protection from fine dusts, fumes and fibres and aqueous mists. Conforms to EN149.

Moulded Mask with Carbon Layer, JSP UK, Model-FFP2-823, Flexi net (TS RP 0059)

Disposable Mask FFP2 - 823 odour valved (medium / large) activated carbon layer is incorporated to remove nuisance odour.



Particulate Respirator, JSP UK, Model-N95 (TS RP 0060)

42CFR84 123 particulate respirator N95 niosh approval, 95% filter efficiency. Level effective against particulate aerosol free from oil.

Respirator Mask with Cartridge, JSP UK, Model-Tradesman 2 AI+P2 (TS RP 0061)

The Tradesman 2 is a maintenance free disposable mask supplied complete with filter cartridges. The mask can be used until the filters expire or up to 28 days whichever occurs first. There is no need to keep COSHH records when using this mask. Manufactured from hypo-allergenic, odour free, medical grade PVC. Conforms to EN405.



Olympus® Midlmask Twin Filter Rubber Mask – Grey, JSP UK (TS RP 0062)

Reshaped economical twin filter mask combines with JSP unfit twin filter cartridges. Wide elastic complete with new head cradle ensures comfortable fit. Sold without filters.

Unifit Cartridge, JSP UK, Model-P2S (TS RP 0063)

The gas, vapour and dust filters are designed to fit the JSP range of midimasks. The full gas and particulate filter range is colour coded to European norms in EN14387 and EN143.



Unifit Cartridge, JSP UK, Model-A1 (TS RP 0064)

Unifit A1 organic vapour cartridge, The gas, vapour and dust filters are designed to fit the JSP range of midimasks. The full gas and particulate filter range is colour coded to European norms in EN14387 and EN143.



Unifit Cartridge, JSP UK, Model-ABEK (TS RP 0065)

Unifit ABEK1 combination vapour cartridge, The gas, vapour and dust filters are designed to fit the JSP range of midimasks. The full gas and particulate filter range is colour coded to European norms in EN14387 and EN143.



Half Mask with Typhoon Valve without Twin Cartridges, JSP UK, Force8 (TS RP 0066)

The Force8™ twin cartridge half mask with Typhoon™ valve offers superior low breathing resistance and a 4-point suspension harness with quick release buckles. The mask is made with a durable thermoplastic rubber offering a superior fit to most face shapes. The mask accepts the full range of low profile Force8™ filters giving the Force8™ the flexibility to be used for many applications, providing filtering protection against particulates, many gases and vapours. Durable thermoplastic rubber mask for superior fit to most face shapes.

Fully adjustable 4-point cradle suspension ensuring an effective facial fit. Reflective strips create increased visibility in low-light environments for added safety. Low resistance exhalation valve for easy breathing, with stable mask configuration conforms to EN140 (Face piece), EN14387: 2004 (Filter range is colour coded to European norms in EN14387 and EN143).

Force8 Range Replacement Filter Cartridges, JSP UK, Model-Force8 710 (TS RP 0067)

F8710 filters feature a low profile angle design for minimal visual impairment, protect against low capacity gas/vapour, organic vapour, inorganic vapour, acidic vapour, ammonia vapour, nuisance odour, white spirit, chlorine, brick acid, formaldehyde. Conforming to EN14387: 2004.



Force8 Range Replacement Filter Cartridge, JSP UK, Model-F8110 (TS RP 0068)

F8110 filters feature a low profile angle design for minimal visual impairment, protect against low capacity gas/vapour, organic vapour, inorganic vapour, nuisance odour, white spirit, Conforming to EN14387: 2004.

Filter Spec, JSP UK (TS RP 0069)

The unique patented FilterSpec® effortlessly combines both eye & respiratory protection. The one-piece lens offers optimal coverage and has anti-mist and anti-scratch coating as standard. FMP2 filtration giving 94% efficiency. FilterSpec® out exceeds EN1827 for breathing resistance by more than HALF and performs over 3% above the standard for filtration efficiency. Includes white holder, 3 filters and spectacle with clear HC & Anti-mist lens.



FACE PROTECTION

Face Shield China (TS RP 0070)

Yellow color brow guard with wheel ratchet harness and splash proof polycarbonate visor.



Face Shield Spring type, China (TS RP 0071)

Aluminum visor carrier to fit on the helmets, with 200mm poly carbonate visor china.

Face shield, JSP UK, Martcare (TS RP 0072)

Grey brow guard with polycarbonate visor with wheel ratchet adjustment. Conforms to EN166.1.B.3.9.



Visor Carrier with 200mm Poly Carbonate Visor, JSP UK (TS RP 0073)

Offer protection against medium energy high speed particles at 270mph, liquid droplets and molten metal. Conforms EN166 1.B.3.



SAFETY VEST

Safety Vest, Net Type, VIKING (TS SV 0074)

100% polyester net, high visibility, 2 front and 2 rear reflective strip of 25mm wide, front velcro fastening – color-lemon green, size small – 4XL.



Safety Vest Net Type, VIKING (TS SV 0075)

100% polyester net, high visibility, 2 front and 2 rear reflective strip of 25mm wide, front velcro fastening – color - orange size small – 4XL.

Safety Vest Net Type, VIKING (TS SV 0076)

100% polyester net, high visibility, 2 shoulder and 2 around the vest reflective strips of 50mm wide, front velcro fastening – color- lemon green, size small – 4XL.



Safety Vest Fabric Type, VIKING (TS SV 0077)

100% polyester fabric, high visibility, 2 shoulder and 2 around the vest reflective strips of 50mm wide, front velcro fastening – color - lemon green, size small – 4XL.

Safety Vest Fabric Type, VIKING (TS SV 0078)

100% polyester fabric, high visibility, 2 shoulder and 2 around the vest reflective strips of 50mm wide, front velcro fastening – color - orange, size small – 4XL.



Safety Vest Executive Type, VIKING (TS SV 0079)

100% polyester net, high visibility, 2 shoulder and 2 around the vest PVC reflective strips of 50mm wide, front zip fastening, cellphone pocket on the left side of chest, transparent pocket for ID on the right side chest, 2 zip fastening pocket on the bottom. Color - lemon green, size small – 4XL.

Safety Vest Executive Type, VIKING (TS SV 0080)

100% polyester net, high visibility, 2 shoulder and 2 around the vest PVC reflective strips of 50mm wide, front zip fastening, cellphone pocket on the left side of chest, transparent pocket for ID on the right side chest, 2 zip fastening pocket on the bottom. Color - orange, size small - 4XL.



Winter Jacket, VIKING (TS SV 0081)

Polyester winter jacket, full sleeve green color with 2 inch reflective straps, 100% nylon interior, front side zip and press button fastening, fold away hood with cord in collar, two full size pocket with flap on front side, Made in china. Conforming to EN 471.



HAND & KNEE PROTECTION

Hand Gloves, VIKING (TS HKP 0082)

Hand gloves H/Duty, double palm leather, VIKING, ART 1103, Gr-10, Make China.



Mechanical Gloves, JSP UK (TS HKP 0083)

Synthetic reinforced rubber & leather palms with gel cushioning for added grip and reinforced thumb and finger tips for added durability. Ventilated fingers for breathability. Spandex knuckle protector for better fit and elasticated hook and loop adjustable wrist fastening.



PVC Dotted Gloves (TS HKP 0084)

Durable cotton fabric with PVC dots on palm and back of index finger extend wear life, superior grip moderate abrasion resistance, excellent comfort, available 8oz, 10oz and 12oz.

Latex Coated Gloves (TS HKP 0085)

10g.5 poly/cotton strands knit liner latex coated gloves.



Knee Pad (TS HKP 0086)

Polyurethane knee pad with button fastening black color.



FOOT PROTECTION

Safety Shoes for Labours, JSP UK, Model-1839 (TS FP 0087)

Safety shoes Model-1839, JSP Oxford, England Conforming to BS / CE EN 20345:2004, steel toe and steel midsole, double density polyurethane sole, shock absorbing heel, antistatic and oil / acid / alkali resistant, pure upper leather, comfort fit, anti slip, anti-bacterial + comfort insole.



Safety Shoes S3, JSP UK, Model-JSP Pioneer (TS FP 0088)

Safety shoes S3 Model-JSP Pioneer, JSP Oxford, England. Conforming to BS / CE EN 20345:2004, steel toe and steel midsole, double density polyurethane sole, shock absorbing heel, antistatic and oil / acid / alkali resistant, pure upper leather, comfort fit, anti slip, anti-bacterial + comfort insole. Sizes available 38-47.

Safety Shoes for Labours VIKING, Model-Classic (TS FP 0089)

Safety shoes, VIKING, Model-Classic, Conforming to BS / CE EN 20345, steel toe and steel midsole, double density polyurethane sole, shock absorbing heel, antistatic and oil / acid / alkali resistant, pure upper leather, comfort fit, anti slip, anti-bacterial + comfort insole. Sizes available 38-47.



Safety Shoes for Labours, VIKING, Model-Alpine (TS FP 0090)

Safety shoes, VIKING, Model-Alpine, steel toe and steel midsole, double density polyurethane sole, shock absorbing heel, antistatic and oil / acid / alkali resistant, pure upper leather, comfort fit, anti slip, anti-bacterial + comfort insole. Sizes available 38-47.

Safety Shoes for Executive Staff, JSP UK, Model-2688 (TS FP 0091)

Executive type conforming to BS / CE EN 20345:2004, black Model-2688, JSP UK with composite toe and midsole, air light lining, pure leather upper, light weight double density polyurethane sole, shock absorbing sole, comfort fit, oil / acid/ alkali resistant, antistatic, anti slip. sizes available 38-47.



Safety Shoes for Executive Staff, VIKING (TS FP 0092)

Executive type, black, VIKING, conforming to BS/CE EN20345:2004, composite toe and midsole, air light lining, pure leather upper, light weight double density, polyurethane sole, shock absorbing sole, comfort fit, oil/Acid/ alkali resistant, antistatic, anti slip. Sizes available 38-47.

Safety Shoes for Welders, JSP UK, Model-1589 (TS FP 0093)

Safety shoes for welders Model-1589, JSP Oxford, England conforming to BS/ CE EN 20345:2004, C/w steel toe and steel midsole, double density polyurethane sole, shock absorbing heel, antistatic and oil / acid / alkali resistant, pure upper leather, comfort fit, anti slip, anti-bacterial + comfort insole. Sizes available 38-47.



Safety Steel Toe Gumboot / WELLINGTONS Silber ITALY (TS FP 0094)

Wellington gumboot with steel toe and midsole, silber brand, Italy make, Conforming to EN20345, sizes available 39 to 47.



FALL PROTECTION

Safety Full Body Harness, PROTECTA FRANCE, Model-AB1000 (TS FP 0095)

1 fall arrest dorsal D ring, adjustable thigh straps, adjustable chest strap, webbing polyester width 45 mm, stitching: high-strength polyamide thread, breaking strength > 2500 daN Fitting : high-strength zinc-plated steel, attachment D rings in zinc-plated wrought steel, energy, absorbing dorsal plate, quick adjustment buckles, system breaking strength : > 1500 daN, Conforming to CE EN361.



Work Restraint Rope Lanyard, Protecta France, Model-AL4000 (TS FP 0096)

Braided 10.5mm rope with slip buckle to adjust to desired length up to 1.8 mtr. Conforming to EN 354.



Karabiner Hook CT15 (TS FP 0097)

Karabiner hook, screw karabiner 15mm opening conforming to EN362.

Safety Full Body Harness, Delta Plus - All Safe, Model-H2000/E1 (TS FP 0098)

Full body harness with one anchorage point and two points of adjustment. Conforming to EN361, webbing width – 45mm, breaking strength – 5000 lbs.



Safety Full Body Harness Delta - Plus All Safe, Model-H2000/1MFB (TS FP 0099)

Full body harness with one anchorage point and six point of adjustment. Sliders for chest strap with tool hangers. Conforming to EN361, webbing width – 45mm, breaking strength – 5000 lbs.

Safety Full Body Harness Delta-Plus All Safe, Model-H2000/2MFB (TS FP 0100)

Full body harness with two anchorage points and six points of adjustment. Sliders for chest strap with tool hangers conforming to EN361.



Safety Full Body Harness, Delta Plus-All Safe (TS FP 0101)

Full body harness with one anchorage point and six point of adjustment. Sliders for chest strap with tool hangers. Incorporated with a comfortable belt for work positioning having two side's attachment and one point of adjustment. Conforming to EN361 and EN 358.

Safety Full Body Harness, Delta - Plus All Safe, Model-HAR 35TC (TS FP 0102)

Two colour harness with belt: 2 fall arrester anchorage points (back - front). Positioning belt with thermoformed back and shorts. 2 work positioning attachment points (lateral). 1 suspension point. 8 adjustable buckles. 1 karabiner. Conforming to EN361, EN358 and 813, 1.9kg weight.



Derrick Harness, Delta-Plus All Safe, Model-HAR46D (TS FP 0103)

DERRICK harness with one rear anchorage point provide with 0.5m extension lanyard. Comfortable work positioning belt with two side attachments and one rear attachment for restrain. Thigh strap with comfortable pads. Automatic aluminized buckle for easy donning. Removable front belt with two attachment for monkey board operations. Conforming to EN361, EN358.



Safety Belt, Delta-Plus All Safe, Model-EX120 RL 150C (TS FP 0104)

Positioning belt with thermoformed back. 2 lateral anchorage points for work positioning. 1 adjustment loop. Sponge back lining 1,5m rope lanyard and karabiner. Conforming to EN358.



Rope Lanyard 1.8 mtr for the Harness (TS FP 0105)

Rope lanyard 1.8 mtr for the harness one side thimble eye and other side soft eye. CE0086-conforming to EN354:2010.



Karabiner Hook (TS FP 0106)

Screw lock karabiner 15 mm opening for harness, Zinc coated steel conforming to EN362.



Shock Absorber, Delta-Plus, Model-AN209CD (TS FP 0107)

Fall arrester with energy absorber on 27mm width single webbing lanyard. Energy dissipater protected a textile sheath with 1 karabiner hook and 1 scaffolding hook. Conforming to EN355 and EN362.

Shock Absorber, Delta-Plus Froment, Model-AN219CDD (TS FP 0108)

Fall arrester with energy absorber on 27mm width double webbing lanyard. Energy dissipater protected a textile sheath with 1 karabiner hook and 2 scaffolding hook. CE - EN355 and EN362.



Fall Arrester Device, Delta-Plus Froment, Model-AN063 (TS FP 0109)

Sliding non opening fall arrester device with 12mm dia three strand rope available in various length. CE - EN353-2.



Fall Arrester Device, Delta-Plus Froment, Model-AN060 (TS FP 0110)

Fall arrester opening type sliding on anchorage line standard rope 14mm dia in various length equipped with automatic locking, non-Inverting device, energy absorber with fall indicator. CE - EN353-2.

Fall Arrester on Flexible Anchorage Line, Delta-Plus Froment, Model-AN066 (TS FP 0111)

Cameleon, sliding fall arrester on braided rope 10mm dia anchor line CE – EN353-2, EN358 and EN12841.



Mini Bloc, Delta-Plus Froment-AN102 (TS FP 0112)

Self-retractable fall arrester with 46 mm strap with energy absorber, protector case, 1 karabiner hook. CE EN360.

Self-Retractable Fall Arrester, Delta-Plus Froment, Model-AN153, AN 154, AN115, AN116t (TS FP 0113)

Self-retractable fall arrester with 4mm dia galvanized steel cable with integrated energy absorber, ABS case, fall Indicator, inertia locking system. Available in 10 mtr, 15mtr, 20mtr, 25 mtr. CE – EN360.



Retractable Fall Arrester, Delta-Plus Froment, Model-Med loc AN13006C (TS FP 0114)

Self retractable fall arrester with polyester webbing 25mm. ABS protection. Swivel with fall indicator. 1 carabiner AM002.

Tool Lanyard, Delta-Plus All Safe (TS FP 0115)

Extensible tool hanging lanyard with a capacity of 2kg, length 1.2 mtr Delta Plus. Model WALTL 1200.



Bosun Seat, Delta-Plus All Safe (TS FP 0116)

Comfortable bosun seat for vertical movement. Length adjustable foot rest for better stability. Tool hanging D-rings on both sides.

Tripod Delta-Plus All Safe, Model-TR020 (TS FP 0117)

Telescopic tripod in galvanized steel, adjustable height 1.45 mtr to 2.15 mtr, maximum wheelbase of 1.50 mtr on the ground. 1 central anchorage ring for a fall arrest. Able to attach an adjustment board TR101 or TR102 for a self-retracting fall arrest.



Manual Winch, Delta-Plus, Model-TR003C (TS FP 0118)

Manual winch in galvanized cable. Length 20mtr, non-return system, folding handle. Load capacity 300kg.

Manual Winch, Delta-Plus, Model-TR004 (TS FP 0119)

Manual winch in galvanized cable. Dia 4mm x length 20mtr, non-return system, Load capacity 300 kg.



First Aid Box, VIKING USA (TS FP 0120)

Made of white poly box with first aid instruments and bandages-available for 10 person, 25 person, 50 person. Conforming to ANSI-Z308.1 2009.

Disposable Coverall - 40 gsm (TS FP 0121)

Woovenfabric disposable coverall with front zip fastening and hood.





TRAFFIC CONES AND POSTS



Traffic Cone 1Mtr., JSP England (TS TCP 0122)

Traffic cone 100cm height JSP, open top with groove, 39cm reflective sleeve, with heavy-duty 570 mm x 570mm x 45mm thick JSP black PVC recycled base, 6.8kg weight.



Traffic Cone 1 Mtr. VIKING (TS TCP 0123)

Traffic cone 100cm height VIKING, open top with groove, 39cm reflective sleeve, with 530mm x 530mm x 25mm thick VIKING black recycled PVC base 5-5.5 kg weight.

Traffic Cone 1Mtr., VIKING + JSP (TS TCP 0124)

Traffic cone 100cm height VIKING, open top with groove, 39cm reflective sleeve, with heavy-duty 570 mm x 570mm x 45mm thick JSP black rubber base, 6.8kg weight.



Traffic Cone 1 Mtr. (TS TCP 0125)

Traffic cone 100cm height China make closed top with 30cm reflective sleeve, with normal rubber base 5kg weight.

Traffic Cone 75 cm Height China (TS TCP 0126)

Traffic cone 75 cm height with 38cm x 38cm black base and reflective sleeve, 2.8kg weight.



Traffic Cone 50 cm Height China (TS TCP 0127)

Traffic cone 50 cm height with 30cm x 30cm black base and reflective sleeve, 2kg weight.

PVC Flexible Soft Traffic Cone 90cm, Turkey (TS TCP 0128)

PVC flexible soft single traffic cone, unbreakable, 90cm height, fluorescent orange color, open top with loop, 2 reflective sleeves, 38cm x 38 cm base 3.6 Kg weight.



PVC Flexible Soft Traffic Cone 90cm, China (TS TCP 0129)

PVC flexible soft single traffic cone, unbreakable, 90cm height, fluorescent orange color, open top, 2 reflective sleeves 37cm x 37cm base 4Kg weight.

PVC Flexible Soft Traffic Cone 70cm, China (TS TCP 0130)

PVC flexible soft single traffic cone, unbreakable, 70cm height, fluorescent orange color, open top, 2 reflective sleeves, 35cm x 35cm base 2.3Kg weight.



PVC Flexible Soft Traffic Cone 45cm, China (TS TCP 0131)

PVC flexible soft single traffic cone, unbreakable, 45cm height, fluorescent orange color, open top, 1 reflective sleeves, 30cm x 30cm base 1.8Kg weight.

PVC Flexible Soft Cone 30 cm Height China (TS TCP 0132)

PVC fluorescent orange color, open top, 1 reflective sleeves, 21cm x 21cm base 600g weight.



PVC Flexible Soft Cone (TS TCP 0133)

PVC flexible soft cone, high quality traffic cone in different colors.

PVC Only Insert for 1Mtr Traffic Cone, VIKING (TS TCP 0134)

Traffic cone without Rubber base 100cm height VIKING, open top with groove, 39cm reflective sleeve.



PVC Only Insert for 1Mtr Traffic Cone, JSP UK (TS TCP 0135)

Traffic cone without Rubber base 100cm height JSP UK with open top and groove, 39cm reflective sleeve.

Flexible Delineator Post 75 cm, VIKING (TS TCP 0136)

Road line delineator 80mm Dia x 750mm height, with 3 reflective sleeve of 70mm height, is made of polyurethane which is strong against crashes and shocks. It is very flexible so as to not damage the vehicle at collision and can be restored soon to its original condition, 3 sets of Anchor bolts M8x50 at base can be removed without damage on surface of asphalt since the shield can be left in the asphalt when removing the flexible post only. It has an excellent recovery and the pole does not break away from the base.



PVC Spring Back Type Delineator Post 80 cm, VIKING (TS TCP 0137)

Moulded post with integral shock cord device allows post to revert to upright after impact. Comes complete with sealbrite sleeve, eye on top, black rubber base with 3 holes to screw the fixing bolts. 80 cm height x 100mm Dia.



PVC Spring Back Type Delineator Post 120 cm, VIKING (TS TCP 0138)

Moulded post with integral shock cord device allows post to revert to upright after impact. Comes complete with sealbrite sleeve, eye on top, black rubber base with 3 holes to screw the fixing bolts. 120 cm height x 100mm Dia.



T TOP Post 115 cm (TS TCP 0139)

T Top Post 115cm height with slot on the bottom and reflective sleeve on upper part, with heavy duty octagonal rubber base with hole for easy to carry. Weight 8kg.



Barrier Post 120cm, Model-120 TB404 (TS TCP 0140)

Barrier post red color, 120cm height x 110 mm dia with reflective sleeve, sand filled PVC base, twist attachment socket on top 12 kg weight.



Chain Post with Base, JSP UK (TS TCP 0141)

Chain Support post with cap, red and white color with heavy duty base for securely holds the post and chain, this base is made from a recycled PVC and weighs in at around 3kg 90 cm height, available in red / white, black / yellow colors.



PVC Chain Post China (TS TCP 0142)

PVC chain post china make with water fillable type PVC base, eye cap on top. 90 cm height.



BARRIER AND FENCING

Safety Barrier Fencing Mesh 5kg. VIKING Thailand (TS B&F 0143)

High visibility barrier fencing mesh, 1Mtr width, 50 mtr length, 100GSM, 90 x 30 hole size, weight- 5kg. Available color – orange, yellow, yellow / black, red / white.




Safety Barrier Fencing Mesh 7kg. VIKING Thailand (TS B&F 0144)

High visibility barrier fencing mesh, 1Mtr width, 50 mtr length, 140GSM, 90 x 30 hole size, weight- 7kg. Available color – orange and yellow.

Water Fillable Jersey Barrier 200 cm Length (TS B&F 0145)

PVC, inter locking type water fillable jersey barrier, length - 200 cm, height – 80cm, Top - width 15cm, bottom width – 40 cm, weight – 20kg, inter locking system.



TITAN BARRIER – 2Mtr. Length, JSP UK (TS B&F 0146)

One-piece injection moulded design made from prime grade virgin polypropylene offering sub-zero temperature and 2 year colour fastness properties. The new design is 100% metal free and fully recyclable. Fully reflective panel meeting EN12899-2 requirements.

Expandable Barrier 3 Meter - Yellow / Black, JSP UK, Model-Xpanda (TS B&F 0147)

When closed 550mm which makes it extremely practical for transporting and carrying around. Expanding action gives user length flexibility fixed-length barriers systems do not have. Overall weight of 10.5kg means it is light enough to handle with relative ease but stable enough to hold itself upright in windy conditions, rough ground or hustle and bustle from the public.



Handl – Gard Barrier, ADDGARDS, Model-Handl-Gard (TS B&F 0148)

The professional multi-purpose barrier system for indoor and outdoor safety requirement. 3panel x 800mm height x 970mm width x 30mm thick, set of 3 = 2.7 mtr x 6.4 kg weight.

RIGID Barrier – 2Mtr. length, VIKING (TS B&F 0149)

Rigid barrier, made on HDPE with UV material, Size: length 200cm x width 100cm with engineering grade reflective sleeve, weight - 13 kg, with 360 degree rotatable rubber base.



PVC Expandable Barrier, VIKING (TS B&F 0150)

Light weight expandable barrier can extend the length up to 2.25 m. The design of side stents can be injected water to increase the weight, improving the products' protecting stable performance, the barriers which are pasted high brightness reflective material, height -90 cm weight- 2.2 Kg.

Alu Stretch Single Barrier, VIKING (TS B&F 0151)

Aluminum expandable barrier with powder coating painted in yellow / black colour, height: 95cm, length (open): 300cm, length (close) : 25cm, weight : 6.0kgs.



Alu Stretch Double Barrier, VIKING (TS B&F 0152)

Aluminum expandable barrier with powder coating painted in yellow / black colour, height: 95cm, length (open): 500cm, length (close) : 50cm, weight : 9.6kgs.

Accordion Barrier, VIKING (TS B&F 0153)

Propylene injection molded expandable mobile barrier with 2 castor wheels. Hi-visibility yellow articulating panels form a versatile solution to isolating potential hazards or closing off area for maintenance and other essential service. height: 100cm, length (open) : 380cm length (close): 32cm weight: 16kg.



Safety First Barrier (TS B&F 0154)

Safety first barrier 3 panel of 52cm x 92cm, light weight PVC frame with fluorescent green fabric printed safety first. Easy carry and extend the length with interlocking clamps.

Traffic Warning Smart Drum (TS B&F 0155)

HDPE orange color smart drum is designed to alleviate congestion on construction sites and roads, height - 87cm, dia-53cm, with 2 reflective sleeves, grip on the top for easy handling, black color rubber base for extra grip to the road surface, Made in Korea.





WARNING LIGHTS & BEACONS

Single Battery Flash Light, VIKING, Model-VBF1 (TS B 0156)

Amber color barricade flash light, VIKING, Model-VBF1, luminous source: 6 LEDs, power: 1 no 4R25 6V battery. Equip with 360 degree lens. Standard flash rate in 65+/- 10FPM with metal handle.



Double Battery Flash Light, VIKING, Model-VBF2 (TS B 0157)

Amber color road warning lamp for construction sites, work zones, in-plant work areas, and around highway construction project, 2pcs ultra bright LEDs, Power: 2pcs 4R25 6V battery, Inside switch with photocell make the light dusk on and dawn off Standard flash rate in 65+/- 10 FPM , With plastic handle.

Double Battery Flash Light with Bracket, VIKING, Model-VBF2+B (TS B 0158)

Amber color road warning lamp for construction sites, work zones, in-plant work areas, and around highway construction project, 2pcs ultra bright LEDs, Power: 2pcs 4R25 6V battery, Inside switch with photocell make the light dusk on and dawn off Standard flash rate in 65+/- 10 FPM, With plastic handle and metal bracket.



6 Volt Battery, VIKING, Model-RL996 (TS B 0159)

Spring type terminal, yellow color battery 6 volt, for road warning flash lights.

Solar Power Flash Light, VIKING, Model-VSF1 (TS B 0160)

4PCS super bright LEDs, frequent flashing rate 65+/- 5 FPM, 0.4W solar panel, 1.2V 1500mA Ni-MH rechargeable battery, switch on the lamp bottom with photocell to make the lamp dusk on and dawn off. High Intensity reflective tape on the lens, total height 160mm, dia 90mm available in amber and red colors, blue and green also in steady upon order.



Solar Power Flash Light, VIKING, Model-VSF2 (TS B 0161)

Amber color road warning lamp 4 pcs ultra-bright LEDs, Power: 0.4W rechargeable 1.2 V 1500mAh NI-MH battery, material: PS lens and PP base, outside water-proof switch with photocell make the light dusk on and dawn off, standard flash rate in 65+ 5 FPM, with metal handle and bracket.

Solar Power Flash Light, VIKING, Model-VSF3 (TS B 0162)

Amber color road warning lamp 2PC super bright LED, 7" standard with advanced optics PS lens and PP base, Standard flash rate in 65+/- 5 FPM, outside water-proof switch with photocell make the light dusk on and dawn off.



Solar Power Revolving Light (TS B 0163)

Magnetic base solar power revolving light, Solar Panel 0.65W, 3.6volt, Battery, 1200AhLi, brightness 10000mcd, nominal night range 800 m, horizontal output 360°, vertical output 15°, Degrees of protection IP67, autonomy - can work for 5-7 cloudy and rainy days after being fully charged. Temperature range -25 °C to +70 °C, dimension: 95mm Dia x 145mm height, battery lifespan-3 year.



Revolving Light 3 Bolt Base, VISION ALERT, Model-503.001 (TS B 0164)

Amber color revolving light 3 bolt base, current 4.6A / 2.3A, weight 0.8kg colour image flash rate 160 FPM colour image, pattern rotator, approval 'e' ECE R65, oltage 12V / 24V.



Revolving Light 3 Bolt Base, LAP UK 12/24Volt (TS B 0165)

Revolving light 3 bolt base LED LMB Beacons feature 40 Ultra Bright LEDs that can operate in 3 flash patterns including simulated rotating. Double flash and quad flash EMC approved - ECE R10, dual voltage 12/24V.

Revolving Light 3 Bolt Base, 12 Volt Taiwan, Model-SAI2 (TS B 0166)

Rotary signal lamp is equipped with dome and mounts with 3 bolt and rubber shock-absorbers.

The motor turns at 120-125 rpm Bulb: 10W, DC 12V, Size: 155mm x 94mm.



Revolving Light 3 Bolt Base, 12 Volt, VIKING, Model-VBR3B (TS B 0167)

12volt revolving light with 3 bolt base 55 watt halogen bulb.

Revolving Light, 3 Bolt Base, 12 Volt China Make (TS B 0168)

12volt revolving light with 3 bolt base with 10 watt incandescent bulb.



Revolving Light, 3 bolt base, 220 Volt China Make (TS B 0169)

220volt revolving light with 3 bolt base with 10 watt incandescent bulb.

Magnetic Base Revolving Light, VIKING Taiwan Model-SAM (TS B 0170)

20Watt Ironton revolving light has a magnetic mount and lighter socket adaptor plug connection for the vehicle. Ideal for volunteer fire or rescue squad vehicles, snow-plows and more. Approximately 7in.D x 5.1in.H. sleek, teardrop-shaped amber dome. Available in amber color, 12volt and 24 volts.



Magnetic Base Revolving Light, VIKING, Model-VBRMB (TS B 0171)

12volt revolving light with magnetic base and lighter socket connection adaptor 55 watt halogen bulb.

Magnetic Base Revolving Light, LUCAS UK, Model-LBB760K (TS B 0172)

Magnetic base revolving light with lighter socket connection adaptor voltage – 12/ 24 volt flash rate – 150 FPM ,temperature range: -20 to +50 Degree, lens: polycarbonate, lens colour: amber.



Magnetic Base Revolving Light, VISION ALERT UK, Model-407.001 (TS B 0173)

The aerodynamic design of the 400 series beacon features smooth and quiet belt-driven rotators. The rotator incorporates unique free-form optical reflectors to maximise beam pattern and light output. Fitting - mag 50, current 4.6A, weight 0.8kg, flash rate 160 FPM, flash pattern rotator, approval ECE R65, Voltage 12V / 24V.

Magnetic Base Revolving Light, LAP UK 12/24 Volt (TS B 0174)

Revolving light magnetic base, EMC approved - ECE R10, 12V or dual voltage (12/24V) options, reverse polarity protection, robust design, 70mph rated on magnetic versions, Meets IP56 international protection standards, -30°C to + 50°C extreme temperature reliability, maintenance free direct drive mechanism, high performance ABS base, Non-fading acrylic or polycarbonate lens.



Strobe Flash Light, VISION ALERT UK Model-5E3.000 (TS B 0175)

Strobe flash light vision alert UK Model 5E3.000 heavy duty type 12 / 24Volt.

Xenon Double Flash Light, VISION ALERT UK, Model-583.2DO (TS B 0176)

The midi beacon range offers a different lighting option with aerodynamic low profile styling. Dual voltage 10-48 volt, xenon double flash, 3 bolt base amber color lens.



Blinking Light, VISION ALERT UK 523.001 (TS B 0177)

This popular design of the 500 series standard beacon features a static flash recommended for UK airport use and conforms to CAP168 and ICAO requirements. Our static flash beacon range was designed to exceed the requirements of the latest EMC regulations and feature a single flash rate of 70FPM. Part No: 523.001, Category: Beacons. Voltage 12V, Fitting 3 Bolt.



Solar Flashing Light – Pedestrian Type (TS B 0178)



Material	Monocrystalline silicon 18V/8-10W
Work time	15years
Battery material	Lead-acid, valve-controlled battery, Storage battery 12V/7AH, battery life 3 years, housing PC shell, bend the bracket, pure fiberglass circuit boards
LED Work Time	More than 50,000 hours
LED color	Yellow + Red
LED quantity	145-215PCS
Flashing rate	> 24 ± 2 times/ min
Visual distance	500m
Work time	>240h in the rainy or cloudy
Weight	Varies depending on the product configuration
Controller	Intelligent control microcontroller, and automatic deployment of light-emitting frequency of checks of the product battery capacity, with over charge / discharge protection; band night/ day mode, intelligent operating modes (normal mode and power saving mode); between specific products can be wireless synchronization flicker, no flicker cascade,
Switch	Power switch, mode switch
Power adaptability	Good
Work environment	-20°C +70°C
Waterproof	IP58
Service	Three-year warranty
Packaging	Carton packing
Note	This style can only yellow or reddish slow flash function word (SLOW) function together, the prices of different
diameter	300mm



Air Craft Warning Light, STROBE LIGHT (TS B 0179)

High luminous xenon light for the towers and tower crane, Model-SYF130M, 220 volt, current 0.2A, flash per minute – 70, installation – magnetic, joule 1.5, available in amber, red, blue colors.



Air Craft Warning Light, STROBE LIGHT (TS B 0180)

High luminous xenon light for the towers and tower crane, with lighter socket connection adaptor Model-SYF130DM, 12-110VDC, current 12VDC at 0.22A, flash per minute – 70, installation – magnetic, joule 1.7, available in amber, red, blue colors.



Solar Powered LED Sign Board (TS B 0181)

Size: 60cm x 60cm x 7cm thick, solar panel power: 5W, service life: 15 years rechargeable battery: 12V/17Ah, service life: 2 years LED service life: 100, 000h, LED color: amber/red, visibility distance: 500m, flash frequency: 24-26 times/min runtime: over 240 hours under rainy weather after full charged.

Solar Power Single Side Arrow Board, Reversible (TS B 0182)

Board size: 1800 x 400MM, Solar panel power: 5W, Service life: 15 years, rechargeable battery: 12V/17Ah, service life: 2 years, LED service life: 100, 000h, LED color: amber / red, visibility distance: 500m, flash frequency: 24 - 26 times / min, runtime: over 240 hours under rainy weather after full charge.



Solar Traffic Sign Made In UAE 60 cm (TS B 0183)

Type: active night, color: white, material: aluminum powder coating, certificate: dubai RTA, Size: 60*60*5cm, supply type: solar panel 1 watt, function: 50pcs LED function: 4200mAh battery.

Solar Traffic Sign (TS B 0184)

Dimension: 70*120*5cm body material: aluminum black and white color solar panel: 30watt, more than 20 years life time battery: 12volt 30Ah sealed lead acid LED quantity: 300pcs supper high bright light luminous: 8000mcd included special lens for increasing light lens size: 22mm lens material: polycarbonate working time after full charge: 4 days working time in cloudy weather: 8 days visible distance: more than 1km angle: 150.



12/24 Volt Display Panel Multi-Functional Arrow Light (TS B 0185)

Controller JDX-K4, current <2A, weight 27.5 Kg, wire length 6 mtr, size-158cm x 60cm x 9cm. Base steel plate, illumination intensity- 100-800cd, flash frequency- 60-100n/m, LED -25 set, LED light cover – PC.

Vehicles Roof Mounted Warning Light Bar (TS B 0186)

Top section has 14 clusters – 472 super bright flashing LED lights, two high power alley lights, two high power halogen takedown lights – one facing front of vehicle and other to the rear, six high power flashing marker lights, power cable – 20 Ft. heavy-gauge wire with in-line fuses, illuminated control panel, three rocker switches for independent control of strobe warning lights, marker lights, alley & takedown lights, stainless steel mounting strap for mounting light bar, available in amber, blue, red lens, all models have clear center lens, dimensions: 48-inch length x 12.5-inch width x 9-inch height, available with and without siren.



Solar Powered Multi-Functional Arrow Board Trailer-China (TS B 0187)

Solar panel power: 50W, battery 12V/100AH, visibility distance: over 800m, flash frequency: 40+/-2 times/min, working without solar charging after the full charged - 200Hours, number of LED group: 27pcs of 200 LED, screen size: 2000 x 1800 x 50mm, blue arrow board with reflective sheeting, sign board is foldable while it is not in use on road, stable supports to the trolley while it stands for use, firm construction of trolley makes it reliable for big size board.

LED Traffic Baton Light (TS B 0188)

Materials: ABS handle, transparent tube: polycarbonate, colors: red, green, brightness: 3500MCD, weatherproof, adapts PC casing, compression and non-friable, adapts big power LED, 3 kinds of flash mode, low energy. batteries: 2 D Size, voltage: 3V DC, bulb: 10 LEDs.



Road Safety Guide Robot (TS B 0189)

It is a robot type safety facility, of which appearance is similar to a man, used for protecting field workers working in road works or construction sites and informing the driver of any hazardous situations in advance. Works as one road safety person, labor cost saving, easy to transport and install. Manufactured as a duplex type facility which allows being used for both direction

Simultaneously operation power both AC220V and DC12V battery are applicable power lines of both supply voltage and battery are built-in. Easy to place a signal light bar or flashing light at the ends of both arms. The head and body are manufactured as a single piece of molding and wearing a water-proof raincoat. The volume of the facility can be reduced by bending the upper body and two. Delineator can be attached. Upper body- manufactured as one piece of rotary molding. Lower body- steel frame, costume- a high luminance safety vest is placed on the raincoat. Hand signal light bar can be attached. Arm movement angle 70 degree
Dimension when the robot is installed - 1820H x 470W x 690D
Dimensions when the robot is transported or stored – 980H x 470W x 310D.

Stop and Go Baton Light (TS B 0190)

Materials; ABS handle, PC baton, 17mm dia one side stop written in red color other side vertical arrow in green color with LED.




Wind Sock, AMERICAN FLAG USA (TS B 0191)

18" Dia x 48" and 18" Dia x 60" available with bracket and without bracket.

Brackets for Winsock (TS B 0192)

Frames are constructed of heavy duty wire with sleeve and set collars. Zinc coated for weather protection. Rotate freely with no maintenance required. 18" Throats.



Warning Flag (TS B 0193)

Warning flag with handle available in green, red colors.

Flaring Light for the Vehicles (TS B 0194)

Pulsar rechargeable LED warning lights with main & vehicle chargers- 9 lights mode.



Road Warning Barricade Tape, EUROTape (TS WT 0195)

PVC red and white road warning barricade tape, width 70mm x Length 500mtr x thick 30 micron, each roll packed in individual box, 12 rolls in each Ctn.



Road Warning Barricade Tape, ZEBRA TAPE (TS WT 0196)

PVC road warning barricade tape, width 70mm, x length 250mtr, x thick 30 micron, each roll packed in individual box, 20 rolls in each Ctn. available in red and white, black and yellow, blue and white.

Road Warning Barricade Tape, SUPER STRONG (TS WT 0197)

PVC red and white road warning barricade tape, width 70mm x length 500mtr x thick 50 micron, each rolls packed in individual box, 8 rolls in each Ctn.



Road Warning Barricade Tape, SAFE GUARD (TS WT 0198)

PVC road warning barricade tape, width 70mm x length 300mtr x thick 30 micron, each rolls packed in individual box, 24 rolls in each Ctn. available in green and white, black and orange, black and red, yellow and Red.

Self-Adhesive Reflective Tape (TS WT 0199)

Self-adhesive reflective tape available in red/white, black/yellow, red, white, blue, green colors and different sizes.



Retractable Cone Topper Warning Tape (TS WT 0200)



Our cone retractable topper is a perfect solution to cordon off working areas to create a safer working environment for employees and the public. Simply insert the retractable cone top with barrier belt over a standard traffic cone to create a temporary warning barrier to transform your ordinary line of traffic safety cones into a temporary, cost-effective belt barrier system. It includes a 3 meters retracting belt with locking belt end in your choice of red and white diagonal stripe or yellow and black stripe. It will fit over most standard traffic cones to provide a quick and effective way to restrict access. Ideal for construction sites, work sites, roadside maintenance, engineering applications, and anywhere a temporary barrier or restricted access is required. Belt does not have safety brake.

Retractable cone toppers are more cost effective and easier to use than other metal or wooden barriers. It's an ideal alternative to floor or caution tape: reusable, more visible, more durable.

Barricade Warning Tape (TS WT 0201)

Barricade tape is made of non-adhesive 100 micron thickness polyethylene. Ideal for temporary outdoor or permanent indoor applications, barricade tapes can be tied, stapled or nailed to posts, fences or metal barricades. Available in 50mm width, 70mm width - 100 mtr and 250mtr length, yellow color tape with black text, red color tape with black text, orange color tape with black text, also available desired width, length, color and text.



Plain Warning Tape (TS WT 0202)

Barricade tape is made of non-adhesive 100 micron thickness polyethylene. Barricade tapes can be tied, stapled or nailed to posts, fences or metal barricades. Available in 50mm width, 70mm width-100 mtr and 250mtr length.

PVC Underground Warning Tape for Various Purpose (TS WT 0203)

LDPE warning tape for undergrounds, for electrical cables, telephone cables, fiber optic cables, water pipe line, irrigation pipeline, sewerage pipe line, drainage pipeline, storm water pipeline, fire water pipe line, gas pipeline etc. 100 micron thick, 150 micron thick, 200micron thick – 15cm width, 20cmwidth, 25 cm width - 300 mtr length, 500 mtr length, with text in Arabic and English.



SPEED RAMPS & PARKING ACCESSORIES

Speed Ramps, JSP UK (TS PA 0204)

An exceptionally tough speed ramp made from 100% recycled material, which is available in two heights, 50mm and 75mm for 4mph and 10mph zones respectively. Each Section has an integral interlocking facility for ease of siting and installation. Each inner section has incorporated white reflectors for extra visibility. 40mm x 25mm channel on the underside allowing for hose/cables to be located in. All sections are pre-drilled ready for inserting relevant bolt for specific road surface, i.e. concrete or asphalt

- Dimension Inner:
- a) 50mm high 500mm x 400mm 8.2kg.,
 - b) 75mm high 500mm x 400mm 16kg.
- End Caps:
- a) 50mm high 500mm x 200mm 4.5kg.
 - b) 75mm high 500mm x 200mm 9 kg



Cable Protector-3 Channel (TS PA 0205)

Perfect solution for temporary events such as fairs, conventions, and trade shows; Safety warning symbols molded into lid surface, with universal safety colors for high visibility; Recessed Carrying Handle allows for moving with ease; Easy to interlock Highly visible color Non-conductive construction; Heavy duty Dog-Bone connector interlocks modular sections. Flap Material: PU, Ramp Material: Rubber, Hinge Pin Material: Reinforced Steel Bar, Color: Yellow flap, black ramp.

Length	Width	Height	Channel width	Channel height	Weight
900mm	600mm	75mm	50mm	50mm	18kg

Cable Protector-2 Channel (TS PA 0206)

Perfect solution for temporary events such as fairs, conventions, and trade shows; Safety warning symbols molded into lid surface, with universal safety colors for high visibility; Recessed carrying handle allows for moving with ease; Easy to interlock highly visible color Non-conductive construction; Heavy duty dog-bone connector interlocks modular sections. Flap Material: PU, Ramp Material: Rubber, Hinge Pin Material: Reinforced Steel Bar, Color: Yellow flap, black ramp.



Length	Width	Height	Channel width	Channel height	Weight
1000mm	250mm	50mm	30mm	30mm	7.5kg

Parking Wheel Stopper.183cm (TS PA 0207)



High intensity rubber, firm and useful, special designed, Fix the position accurately, easy installation, black and yellow, international standard, bright color, effectively catch the attention of the drivers. It is widely used in parking lot to protect the corners of the wall and the cars.

Size: length: 183cm, bottom width: 14cm, top width: 6cm, height: 10cm, weight: 22kg with 4pcs install holes.

Parking Wheel Stopper 165cm (TS PA 0208)

High intensity rubber, firm and useful, special designed, fix the position accurately, easy installation, black and yellow international standard bright color, effectively catch the attention of the drivers; It is widely used in parking lot to protect the corners of the wall and the cars.

Size: Length 165cm x width- 14cm height 10cm weight – 13kg, with 3pcs install holes.



Parking Wheel Stopper 50cm (TS PA 0209)



High intensity rubber, firm and useful, special designed, Fix the position accurately, easy installation, Black and yellow, international standard, bright color, effectively catch the attention of the drivers; It is widely used in parking lot to protect the corners of the wall and the cars.

Size: length 50cm x width- 17cm height 14cm weight – 8Kg.

Parking Wheel Choke (TS PA 0210)

Special design to proof skidding. Black rubber wheel chock, easy to move. Rubber car stopper wheel car stopper are used for wedging and blocking tires to restrict with car moving. Size: 20 x 10 x 15cm and 27 x 12 x 18cm.



Rubber Corner Guard (TS PA 0211)

Black rubber corner guard with reflective yellow color diagonal stripes available in 80cm height x 10 cm width x 1cm thick and different sizes.

Remote Control Car Parking Lock (TS PA 0212)

Specifications: Locking height: 300mm, unlocking height: 100mm, Dimension: 64cm x 16cm x 8.5 cm N.W.: 14.5 Kg; It doesn't need to get out of car to lock or unlock the manual parking lock, just do it from the comfort of the driver's seat.

Power Supply: Storage battery (12V 7AH), if 4 times per day, one full charge can last at least three months. Recharge battery takes around 8-10 hours, as simple as charging the mobile phone's battery. When the battery is below 10.5 V, it would automatically make 20 seconds buzz as warning signal every time the user gets it up or down to remind the recharging time. So don't worry the parking lock's going to be a block on the spot when it's flat. It would let you know before its flat. Installation: Only needs 4 special bolts.



Traffic Mirror – Dancop (TS PA 0213)

This mirror foil is 100% aluminum with state-of-the-art protection against moisture and corrosion. TM comes with a solid hot-galvanized fitting with four mounting points and adjustable ball joint. This ensures stability, even in very strong winds. TM mirrors can be mounted on tubular uprights 50-65mm across and by means of special fittings, on tubular uprights up to 85mm in diameter or directly on a wall. Available TMPC model polycarbonate and TMAC acrylic in different sizes.

Poly Carbonate Traffic Mirror, VIKING (TS PA 0214)

Polycarbonate lens + ABS back in orange color with outdoor metal brackets available in 45cm, 60cm, 80cm, 100cm.



Solar Road Stud (TS PA 0215)

Solar cell: poly-crystalline silicon / single-crystalline silicon (2.5v, 95mA)
Storage battery- Ni-MH (1200mAH) / Super Capacitor 50F)
Light source: super luminosity LED, LED quantity: 6 pcs
Luminosity colors: red, yellow. Work time: 108 hours above for Varying Type (150times/minute); and more than 24 hours for constant type (standard luminosity intensity) Work temperature: -25 to +75 degree C.
Material of light: Aluminum alloy and Polycarbonate
Resist compression: 30 tons
Waterproof grade IP>67
Life: >5 years (Ni-MH) or >15 year (Super Capacitor)
View distance: over 800m
Guarantee period: 14 months Size: 12cm x 13 cm



WARNING SIREN

Hand Operated Siren (TS WS 0216)

LK-120 is designed to provide effective warning in applications where there is no power supply. As lightweight, it can be easily transported to remote locations and folds up to a small size for ease of handling Sound Rating: 120±2dB (A) @1M. Output Frequency: 600±20Hz, Effective Range: 1.5km diameter. Net Weight: 9Kg. Carton Size: 45 x 37 x 58CM.



Hand Operated Siren (TS WS 0217)

LK-100 is designed to provide effective warning in applications where there is no power supply. As lightweight, it can be easily transported to remote locations and folds up to a small size for ease of handling. Sound Rating: $110 \pm 2\text{dB (A)}$ @1M. Output Frequency: $550 \pm 20\text{Hz}$. Single Tone, Net Weight: 1.2Kg, Carton Size: 15.5x15.5x16CM.



Electrically Operated Siren (TS WS 0218)

Electric Sirens are widely used as a very effective announcer for Textile Mills, Factories, Workshops, Banks, Ships, Milk Centre, Fire Engines, Police Vans, and Ambulances etc. Available in Horizontal and vertical, single and double mountings. Audible Range – 500 mtr to 3.25 mtr.

Mega Phone, Pro Sound Hand Megaphone (TS WS 0219)

6volt, 20watt, 200mmDia x 330mmL, Function-speech, Siren, Music, Record. Record Time- 10 seconds, with built in extra Microphone, ABS housing, 1Kg weight, Sound cover Range- 300 Mtr.



SIGN BOARDS

Caution Boards (TS SB 0220)

Caution board, A shape free-standing double side plastic yellow board with deferent text- wet floor, Maintenance in progress, Work in progress, Cleaning in progress. Size: height -60cm, Bottom width- 30cm, Top width- 21cm.



Permanent Traffic Sign Boards (TS SB 0221)

Traffic sign made on 3mm aluminum sheet covered with high intensity reflective sheeting in different sizes and messages.

Temporary Traffic Sign Boards (TS SB 0222)

Traffic sign made on 22bwg GI sheet covered with engineering grade/ commercial grade reflective sheeting in different sizes and messages.



Safety Signs (TS SB 0223)

Safety signs made on self-adhesive vinyl for prohibition signs, warning signs, mandatory signs and Information signs for Indoor use in different sizes and messages.

Scaffolding Tag (TS SB 0224)

Scaffolding tag- scaffolding holder with 2 labels, available China make and Malaysia.



LIFTING & LASHING SOLUTIONS

Polyester Webbing Slings (TS LS 0225)

Polyester webbing sling safety factor 7:1 BS EN 1492, safety factor 6:1, size: from 1 inch to 12 inch width, single ply, 2ply, 3Ply, 4ply. Round sling various sizes.



Cargo Lashing Belt with Ratchet (TS LS 0226)

Cargo lashing available from 1 inch – 4 inch width and lashing capacities ranging from 400 kg to 5000kg.

MISCELLANEOUS

Asphalt Rake, BULLDOG UK (TS M 0227)

Heavy duty 47cm width blade with 16 teeth and 174cm long wooden handle specially made for the asphalt.



Stainless Steel Binding Straps, Clips, Tools, BAND-IT UK (TS M 0228)

Available in nonmagnetic stainless steel, 201 stainless steel, 316grade stainless steel. Sizes: 1/4", 1/2", 5/8", 3/4".

Stainless Steel Binding Wire (TS M 0229)

Stainless steel wire, 1.2mm, 18Bwg, 304 grade and 316 grade.



Oil Spill Kits, JSP UK (TS M 0230)

Spill kits help you respond to spills quickly and effectively. Available in fix mount or portable to allow to position in strategic areas of your facility. Controls odours caused by spills to ensure that your workplace can quickly get back to normal after accidental spills. Select the right spill kit for those emergency spills in your workplace or other environments where an emergency spill kit will provide immediate response to chemical spills, oil spills cleanup.

Oil spill kits repel water and will absorb oil only. These oil spill kits are offered in bagged spill kits, wall mount, carts, kit spill trucks, over pack spill kits and many other spill response kit configurations. Available in 15 liter, 35 liter, 90 liter, 150 liter.



Chemical Spill Kits, JSP UK (TS M 0231)

Spill kits help you respond to spills quickly and effectively. Available in fix mount or portable to allow to position in strategic areas of your facility. Controls odours caused by spills to ensure that your workplace can quickly get back to normal after accidental spills.

Select the right spill kit for those emergency spills in your workplace or other environments where an emergency spill kit will provide immediate response to chemical spills, oil spills cleanup.

Chemical spill kits absorb acids and bases and are generally used for environments where chemical spill can occur and need immediate chemical spill cleanup. In general, spill response kits are used for general spill cleanup of oil, coolants, solvents and water based spills. These spill kits are known as MRO spill response kits for the general cleanup of fluids found in many industrial workplaces. Truck spill kits are also very popular among freight transporters for the cleanup of fuel spills. These emergency spill response kits fit tight spaces on vehicles and equipment. Available in 15 liter, 35 liter, 90 liter, 150 liter.

Shading Net (TS M 0232)

Shading net green color available 70% shade and 90 % shade. Sizes: 2x 40 mtr, 3 x 40 mtr, 4 x40 mtr.



Fire Blanket Viking (TS M 0233)

Non-woven fiber glass fire blanket, available in 4ft x 6ft, 6ft x 6ft.



Helmet Shade (TS M 0234)

100% cotton white color shade for helmet.





Tulip Trading L.L.C.

P.O. Box: 25732, Dubai, United Arab Emirates
Tel : + 971 4 3476300, Fax : +971 4 3476343
E-mail: info@tulipsafety.com
www.tulipsafety.com

Deira - Tel: +971 4 2233628 |
MAKANI No. 29323 95970

Fax: +971 4 3476343

Al Quoz - Tel: +971 4 3476300
MAKANI No. 20701 78981